

PROLINE 610



Grassline Technology –For Professionals

WWW.MALONEFM.COM

PROLINE 610



The Malone Proline 610 Rake is built exclusively for the intended use in the agriculture sector for the raking of common grass and cereal crops. The twin rotor rake follows the contours of the ground efficiently using the weight of the rotors on the ground and a single acting ram in the flotation position. The rake is fitted with a control box to allow the user to lift one side of the rake at a time. Making the job as efficient and easy as possible.

The Proline rake is a necessary unit for any and all grass cutting procedures. The rake efficiently rows grass at a width if 6.1m.

The lift tines gently gather and row the grass to be ready to be collected. The rake is perfect for after tedding to easily gather loose grass.

Features

Lift Tines | Swarth Width Adjustment | Steering Axle | Height Adjustment | Rear Lights | Spare Wheel

Lift Tilles Swartif Width Adjustifient Steering Axie Fleigh	
Model	610
Working Width	6.1m (20ft)
Transport Width	2.65m (9ft)
Transport Height	3.8m (12.5ft)
PTO Speed	540rpm
Power Requirement	37kw (50hp)
Number of Rotors	2
Rotor Diameter	2.8m (9.5ft)
Tine Arms per Rotor	11
Tines per Arm	4
Max Sward Width	1.7m (6ft)
Minimum Sward Width	1.3m (4.5ft)
Height Adjustment	150mm (6")



Malone Farm Machinery Ltd.

Ballyglass, Claremorris, Co. Mayo, Ireland, F12 AP11 P. | +353 (0)94 936 0501 W. | www.malonefm.com

Sales Ireland & International

Fearghail Connolly | +353 (0)87 0611 333 Email | sales@malonefm.com

Sales & Services UK

Simon Gilbert | +44(0) 7825 647986 Email | simon.gilbert@malonefm.com